

Flange Mount	Model	Shaft End	Model	Shaft End	Model	Shaft End
	66-200-A	Driven	66-200-B	Driven	66-200-C	Driven
	66-200-A1	Non-Driven	66-200-B1	Non-Driven	66-200-C1	Non-Driven

Note: For each Type A or A1 bearing block required, add .125" to ballscrew thread length.

Cut-Off Flange Mount	Model	Shaft End	Model	Shaft End	Model	Shaft End
	66-300-A	Driven	66-300-B	Driven	66-300-C	Driven
	66-300-A1	Non-Driven	66-300-B1	Non-Driven	66-300-C1	Non-Driven

Note: For each Type A or A1 bearing block required, add .125" to ballscrew thread length.

Base Mount	Model	Shaft End	Model	Shaft End	Model	Shaft End
	66-400-A	Driven	66-400-B	Driven	66-400-C	Driven
	66-400-A1	Non-Driven	66-400-B1	Non-Driven	66-400-C1	Non-Driven

Note: For each Type A or A1 bearing block required, add .125" to ballscrew thread length.

Standard Drive Extension	Mounting Hole Detail	Model Number Designation												
		<p>66 - X 0 0 - X X</p> <p>Bearing Block</p> <p>Mounting Style 2 = Flange</p> <p>3 = Cut-Off Flange 4 = Base</p> <p>.625 Diameter Ballscrew</p> <p>Shaft End Blank = Driven 1 = Non-Driven</p> <p>Bearing Type A = Radial B = Duplex C = Spaced</p>												
<p>Note: Special lengths available.</p>	<table border="1"> <thead> <tr> <th>Mounting</th> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>Base</td> <td>5/16-24</td> <td>1/4-20</td> <td>0.500</td> </tr> <tr> <td>Flange & Cut-Off Flange</td> <td>5/16-24</td> <td>1/4-20</td> <td>0.500</td> </tr> </tbody> </table>	Mounting	A	B	C	Base	5/16-24	1/4-20	0.500	Flange & Cut-Off Flange	5/16-24	1/4-20	0.500	
Mounting	A	B	C											
Base	5/16-24	1/4-20	0.500											
Flange & Cut-Off Flange	5/16-24	1/4-20	0.500											

- Notes**
- All dimensions in inches unless otherwise specified.
 - Refer to Page 3 for Nominal Load Capacities.
 - End journals must be machined per dimensions on Page 13.
 - Custom and metric bearing block assemblies and/or drive end journals are available.
 - Dimensions and specifications subject to change without notice.