

Flange Mount	Model	Shaft End	Model	Shaft End	Model	Shaft End
<p>End View</p>	66-202-A	Driven	66-202-B	Driven	66-202-C	Driven
	66-202-A1	Non-Driven	66-202-B1	Non-Driven	66-202-C1	Non-Driven

Note: For each Type A or A1 bearing block required, add .125" to ballscrew thread length.

Cut-Off Flange Mount	Model	Shaft End	Model	Shaft End	Model	Shaft End
<p>End View</p>	66-302-A	Driven	66-302-B	Driven	66-302-C	Driven
	66-302-A1	Non-Driven	66-302-B1	Non-Driven	66-302-C1	Non-Driven

Note: For each Type A or A1 bearing block required, add .125" to ballscrew thread length.

Base Mount	Model	Shaft End	Model	Shaft End	Model	Shaft End
<p>End View</p>	66-402-A	Driven	66-402-B	Driven	66-402-C	Driven
	66-402-A1	Non-Driven	66-402-B1	Non-Driven	66-402-C1	Non-Driven

Note: For each Type A or A1 bearing block required, add .125" to ballscrew thread length.

Standard Drive Extension	Mounting Hole Detail	Model Number Designation
		<p>66 - X 0 2 - X X</p> <p>Bearing Block</p> <p>Mounting Style 2 = Flange</p> <p>3 = Cut-Off Flange 4 = Base</p> <p>1.000 Diameter Ballscrew</p> <p>Shaft End Blank = Driven 1 = Non-Driven</p> <p>Bearing Type A = Radial B = Duplex C = Spaced</p>

Note: Special lengths available.

Notes

- All dimensions in inches unless otherwise specified.
- Refer to Page 3 for Nominal Load Capacities.
- End journals must be machined per dimensions on Page 13.
- Custom and metric bearing block assemblies and/or drive end journals are available.
- Dimensions and specifications subject to change without notice.