

Flange Mount	Model	Shaft End	Model	Shaft End	Model	Shaft End
	66-206-A	Driven	66-206-B	Driven	66-206-C	Driven
	66-206-A1	Non-Driven	66-206-B1	Non-Driven	66-206-C1	Non-Driven

Note: For each Type A or A1 bearing block required, add .250" to ballscrew thread length.

Cut-Off Flange Mount	Model	Shaft End	Model	Shaft End	Model	Shaft End
	66-306-A	Driven	66-306-B	Driven	66-306-C	Driven
	66-306-A1	Non-Driven	66-306-B1	Non-Driven	66-306-C1	Non-Driven

Note: For each Type A or A1 bearing block required, add .250" to ballscrew thread length.

Base Mount	Model	Shaft End	Model	Shaft End	Model	Shaft End
	66-406-A	Driven	66-406-B	Driven	66-406-C	Driven
	66-406-A1	Non-Driven	66-406-B1	Non-Driven	66-406-C1	Non-Driven

Note: For each Type A or A1 bearing block required, add .250" to ballscrew thread length.

Standard Drive Extension	Mounting Hole Detail	Model Number Designation
		<p>66 - X 0 6 - X X</p> <p>Bearing Block</p> <p>Mounting Style 2 = Flange</p> <p>3 = Cut-Off Flange 4 = Base</p> <p>2.250 Diameter Ballscrew</p> <p>Shaft End Blank = Driven 1 = Non-Driven</p> <p>Bearing Type A = Radial B = Duplex C = Spaced</p>

Note: Special lengths available.

- Notes**
- All dimensions in inches unless otherwise specified.
 - Refer to Page 3 for Nominal Load Capacities.
 - End journals must be machined per dimensions.
 - Custom and metric bearing block assemblies and/or drive end journals are available.
 - Dimensions and specifications subject to change without notice.